



General Description:

MM-BPD-010040-03 is a 3-Way Power Divider operating over the 1.0 to 4.0 GHz frequency range. This model has a maximum insertion loss of 1.2 dB and has very good phase and amplitude match. The compact housing is outfitted with SMA female connectors.

Features:

- Ultra Wide Band: 1.0-4.0 GHz
- Ultra Broadband, Multi-Octave
- Superior Phase & Amplitude Balance

Applications:

- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications :

Parameter	Value			Units
	Min	Typ	Max	
Frequency Range	1.0		4.0	GHz
Insertion Loss			1.2	dB
VSWR			1.4	:1
Isolation	18			dB
Amplitude Balance			±0.5	dB
Phase Balance			±7	°
Power Handling			30	W
Impedance		50		Ohms

Mechanical Specifications:

Parameter	Value
Length	90 mm
Width	46 mm
Height	11 mm
Material / Finishing	Aluminum/Black Paint
RF Connector	SMA Female



Mountain Microwave


Focus on the future

Broadband Power Divider

MM-BPD-010040-03

1.0-4.0 GHz, 3-Way

Outline Drawing:



Environmental Conditions:

Parameter	Standard	Description
Operational Temperature		-45 ~+85
Storage Temperature		-55 ~+125
Random Vibration	MIL-STD-883K, Method 2026, Cond. IB	50 - 2000 Hz, 7.3 Grms
Humidity	MIL-STD-202, Method 103B, Cond. B	100% RH at 35c, 95%RH at 40
Altitude	MIL-STD-883K, Method 1001, Cond. C	50,000 feet

Please note, all information contained in this data sheet is subject to change without notice.

ver 1.0 0618