



**General Description:**

MM-BPD-080124-03 is a 3-Way Power Divider operating over the 8.0 to 12.4 GHz frequency range. This model has a maximum insertion loss of 1.2 dB and has very good phase and amplitude match. The compact housing is outfitted with SMA female connectors.

**Features:**

- Ultra Wide Band: 8.0-12.4 GHz
- Ultra Broadband, Multi-Octave
- Superior Phase & Amplitude Balance

**Applications:**

- Radar Systems
- Communication Systems
- Receivers Systems

**Electrical Specifications :**

Parameter	Value			Units
	Min	Typ	Max	
Frequency Range	8.0		12.4	GHz
Insertion Loss			1.2	dB
VSWR			1.6	:1
Isolation	15			dB
Amplitude Balance			±0.4	dB
Phase Balance			± 10	°
Power Handling			30	W
Impedance		50		Ohms

**Mechanical Specifications:**

Parameter	Value
Length	56 mm
Width	40 mm
Height	10 mm
Material / Finishing	Aluminum/Black Paint
RF Connector	SMA Female



Mountain Microwave


Focus on the future

**Broadband Power Divider**

MM-BPD-080124-03

8.0-12.4 GHz, 3-Way

**Outline Drawing:**



**Environmental Conditions:**

Parameter	Standard	Description
Operational Temperature		-45 ~+85
Storage Temperature		-55 ~+125
Random Vibration	MIL-STD-883K, Method 2026, Cond. IB	50 - 2000 Hz, 7.3 Grms
Humidity	MIL-STD-202, Method 103B, Cond. B	100% RH at 35c, 95%RH at 40
Altitude	MIL-STD-883K, Method 1001, Cond. C	50,000 feet

Please note, all information contained in this data sheet is subject to change without notice.

ver 1.0 0618