



General Description:

MM-BPD-040440-08 is a 8-Way Power Divider operating over the 4.0 to 44.0 GHz frequency range. This model has a maximum insertion loss of 3.8 dB and has very good phase and amplitude match. The compact housing is outfitted with 2.4 mm female connectors.

Features:

- Ultra Wide Band: 4.0-44.0 GHz
- Ultra Broadband, Multi-Octave
- Superior Phase & Amplitude Balance

Applications:

- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications :

Parameter	Value			Units
	Min	Typ	Max	
Frequency Range	4.0		44.0	GHz
Insertion Loss			3.8	dB
VSWR			2.0	:1
Isolation	14			dB
Amplitude Balance			± 1.2	dB
Phase Balance			± 12	°
Power Handling			20	W
Impedance		50		Ω

Mechanical Specifications:

Parameter	Value
Length	111.0 mm
Width	56 mm
Height	10 mm
Material / Finishing	Aluminum/Black Paint
RF Connector	2.4 mm Female




Focus on the future

Broadband Power Divider

MM-BPD-040440-08

4.0-44.0 GHz, 8-Way

Outline Drawing:



Environmental Conditions:

Parameter	Standard	Description
Operational Temperature		-45°C~+85°C
Storage Temperature		-55°C~+125°C
Random Vibration	MIL-STD-883K, Method 2026, Cond. IB	50 - 2000 Hz, 7.3 Grms
Humidity	MIL-STD-202, Method 103B, Cond. B	100% RH at 35c, 95%RH at 40°C
Altitude	MIL-STD-883K, Method 1001, Cond. C	50,000 feet

Please note, all information contained in this data sheet is subject to change without notice.

ver 1.0 0418