



**General Description:**

MM-MPA-092096-20-24 is a Waveguide Power Amplifier that operates over the frequency range of 92 to 96 GHz. This model provides a typical gain of 20 dB . It provides a Psat of 24 dB typical and operates on +16 VDC with a typical current draw of 280 mA.

**Features:**

- Ultra Wide Band: 90-96 GHz
- Gain: 20 dB
- Psat: 24 dB
- Internally regulated
- Unconditionally stable

**Applications:**

- Radar Systems
- Communication Systems
- Receivers Systems

**Electrical Specifications (23° C):**

Parameter	Value			Units
	Min	Typ	Max	
Frequency Range	92		96	GHz
Gain		20		dB
Gain Flatness		-		dB
Psat		24		dBm
Output Power (P1dB)		-		dBm
Input VSWR		3.0		:1
Output VSWR		3.0		:1
DC Voltage		16/5		V
DC Current		280/80		mA

**Absolute Maximum Ratings:**

Condition	Value
DC Voltage	+16/5 V
Maximum Input Power(CW)	TBD
ESD sensitivity (HBm)	Class 0, passed 150V

**Mechanical Specifications:**

Parameter	Value
Length	- mm
Width	- mm
Height	- mm
RF Connector	WR10/UG-387



Mountain Microwave

Focus on the future

Waveguide Power Amplifier

MM-MPA-092096-20-24

92 to 96 GHz

**Outline Drawing:**

mm(Inches)

**Environmental Conditions:**

Parameter	Standard	Description
Operational Temperature		-10°C~+40°C
Storage Temperature		-45°C~+125°C
Random Vibration	MIL-STD-883K, Method 2026, Cond. IB	50 - 2000 Hz, 7.3 Grms
Humidity	MIL-STD-202, Method 103B, Cond. B	100% RH at 35c, 95%RH at 40°C
Altitude	MIL-STD-883K, Method 1001, Cond. C	50,000 feet

**Caution:**

- Exceeding absolute maximum ratings shown will damage the device.
- The device is static sensitive. Always follow ESD rules when working with the device.
- Heat Sink required during operation.

Please note, all information contained in this data sheet is subject to change without notice.

ver 2.0 0318